



Lic. # QAC/R91/0805  
Lic. # 1150/2011 CC

## UPTODATE PLASTICS AND PACKAGINGS PRIVATE LIMITED

301 & 316, LAXMI DEEP BUILDING,  
LAXMI NAGAR DISTRICT CENTRE  
VIKAS MARG, DELHI - 92  
Ph.: + 91-11-42448614; 43046510

### Uptodate Plastics and Packagings Private Limited

PRODUCT REALISATION UPP-PROD-7.2.1-F-14 ISSUE/REV.01/00 DATE: 12/05/2016  
REASONS FOR LAST REVISION:

# PRODUCT SPECIFICATION SHEET UPT-1245

#### CHEMICAL CLASSIFICATION:

UPT-1245 (Formerly F - 5245) is a special book binding hot melt adhesive. This product is based on water white, low odour, hydrogenated resin. This is a premium grade hot melt adhesive for side gluing in perfect binding machines having a separate side glue tank. The product has a low viscosity and long open time.

#### PROPERTIES:

Type:	Synthetic, hot melt adhesive
Mode:	Rollers
Surface Touch:	Light Ambient Tack
Form:	Granules
Colour:	Water-white
Softening Range:	65°C - 75°C
Application Temperature:	140°C - 160°C
Specific Gravity:	0.96
Water Absorption:	Not Determinable
Stability:	20 Hrs. at 150°C
Viscosity:	2,500 - 3,500 cPs@170°C
Shelf Life:	12 - 18 months @ < 30°C
Open Time:	Long

12/05/2016

#### IMPORTANT

The information contained in this write-up is to the best of our knowledge, true and accurate, but any recommendations or suggestions included are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained here in shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Specification Sheets are modified from time to time based on improvements carried out. Always ensure that the latest Specification Sheet is referred.