



Lic. # QAC/R91/0805
Lic. # 1150/2011 CC

UPTODATE PLASTICS AND PACKAGINGS PRIVATE LIMITED

301 & 316, LAXMI DEEP BUILDING,
LAXMI NAGAR DISTRICT CENTRE
VIKAS MARG, DELHI - 92
Ph.: + 91-11-42448614; 43046510

Uptodate Plastics and Packagings Private Limited

PRODUCT REALISATION UPP-PROD-7.2.1-F-14 ISSUE/REV.01/00 DATE: 12/05/2016
REASONS FOR LAST REVISION:

PRODUCT SPECIFICATION SHEET UPT-1356

CHEMICAL CLASSIFICATION:

UPT - 1356 is a premium grade hot melt adhesive used for spine gluing in perfect binding machines. This product is based on low odour, hydrogenated resins. This grade is recommended for spine gluing in one-shot automatic-binding machines for manufacture of magazines, catalogues, timetables and paperbacks.

PROPERTIES:

Type:	Synthetic, hot melt adhesive
Mode:	Rollers
Form:	Granules / Chips
Colour:	Water-white
Surface Touch:	No Ambient Tack
Softening Range:	75°C - 85°C
Application Temperature:	160°C - 180°C
Specific Gravity:	0.96
Water Absorption:	Not Determinable
Stability:	20 Hrs. at 150°C
Viscosity:	3,000 - 5,000 cPs@170°C
Shelf Life:	12 - 18 months @ < 30°C
Open Time:	Medium

12/05/2016

IMPORTANT

The information contained in this write-up is to the best of our knowledge, true and accurate, but any recommendations or suggestions included are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained here in shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Specification Sheets are modified from time to time based on improvements carried out. Always ensure that the latest Specification Sheet is referred.