



Lic. # QAC/R91/0805  
Lic. # 1150/2011 CC

## UPTODATE PLASTICS AND PACKAGINGS PRIVATE LIMITED

301 & 316, LAXMI DEEP BUILDING,  
LAXMI NAGAR DISTRICT CENTRE  
VIKAS MARG, DELHI - 92  
Ph.: + 91-11-42448614; 43046510

### Uptodate Plastics and Packagings Private Limited

PRODUCT REALISATION UPP-PROD-7.2.1-F-14 ISSUE/REV.01/00 DATE: 12/05/2016  
REASONS FOR LAST REVISION:

# PRODUCT SPECIFICATION SHEET UPT-8110

#### CHEMICAL CLASSIFICATION:

UPT - 8110 is a high performance, high tack, heat resistant glue stick especially suitable for packaging applications where aggressive tack and heat resistance is required. This stick is also suitable for adhesive bonding of difficult surfaces, e.g. varnished cartons.

#### PROPERTIES:

Type:	Synthetic, hot melt glue stick
Colour*:	Natural Yellow
Form:	Rods ~ 11 mm diameter
Surface Touch:	Non Tacky
Softening Point:	105°C - 115°C
Application Temperature:	Use minimum 60W applicator gun
Specific Gravity:	0.96
Water Absorption:	Negligible
Stability:	20 Hrs. at 150°C
Viscosity:	8,000 - 10,000 cPs @160°C
Open Time:	Short

\* Colour may vary by a shade from batch to batch

12/05/2016

#### IMPORTANT

The information contained in this write-up is to the best of our knowledge, true and accurate, but any recommendations or suggestions included are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained here in shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.

Specification Sheets are modified from time to time based on improvements carried out. Always ensure that the latest Specification Sheet is referred.